

Technical datasheet

Description

Article Number

33979

Type description

REV-5POL/05-7,5kW R/Y, 16A, IP66, 1NC, switch 0/1+mounting kit, red/ yellow

Switching diagram

Emergency-off switch

6 switching contacts

5-pole + 1NC

Switching angle: 90°

Lettering O OFF - I ON

Electrical Data Switch

Rated uninterrupted current I_{the}

25 A

Rated operational current I_e AC-21A

25 A

Rated operational voltage U_e

690 V

Making/breaking capacity of AC-23A 400V

7.5 kW

Making/breaking capacity of AC-3 400V

5.5 kW

Isolating characteristic up to

500 Volt ~

Single phase motor 230V

2.2 kW

Single phase motor 400V

3 kW

Terminal cross section

- solid or multi-stranded min./max. 1.0 - 4.0 mm²

- finely stranded with ferrule min./max. 1.0 - 2.5 mm²

Application

Insulated enclosure I1N1550 UV and weather resistant


Lockout handle for 3 padlocks lockable in O-position

Handle/enclosure

red/yellow

Degree of protection

IP66



Dimensions (mm)

A	C	D	E	G	Knock-out		Drilled
					H1	H2	H3
90.5	73	29	80	Ø5.5	M20	M12	M20

